

# Revolutionizing Heat Transfer and Fluid Flow Models: Fractional Calculus and Non-Newtonian Dynamics Meet Advanced Numerical Methods

Prabhat Kumar<sup>1</sup>, M.M. Dixit<sup>2</sup>, Dr. Neha Verma<sup>3</sup>, Dr.J.Pandima Devi<sup>4</sup>, DR.P.RANI<sup>5</sup>, Dr. Vijay Kumar Dwivedi<sup>6</sup>, Kanchan Yadav<sup>7</sup>

<sup>1</sup>Department of Applied Sciences & Humanities, NERIST, Nirjuli, Department of Mathematics, A.P..  
India-prabhats1718@gmail.com

<sup>2</sup>Department of Applied Sciences & Humanities, NERIST, Nirjuli, Department of Mathematics, A.P..  
India.-mmdixit79@gmail.com

<sup>3</sup>Department of Mechanical Engineering, Shri Shankaracharya Institute of Professional Management and Technology, Raipur, Chhattisgarh 492013, India. n.verma@ssipmt.com

<sup>4</sup>Assistant Professor, Department of Mathematics, NPR College of Engineering & Technology, Natham, Dindigul  
sabarimadhu84@gmail.com

<sup>5</sup>Associate Professor, Department of Mathematics, NPR College of Engineering & Technology, Natham, Dindigul  
ranikathir@gmail.com

<sup>6</sup>Assistant Professor, Department of Mathematics, Vishwavidyalaya Engineering College, Ambikapur (C.G.) 497001  
dwivedi.vk69@gmail.com

<sup>7</sup>Department of Electrical Engineering, GLA University, Mathura, India. kanchan.yadav@gla.ac.in

---

## Article History:

**Received:** 05-08-2024

**Revised:** 10-09-2024

**Accepted:** 21-09-2024

## Abstract:

This research explores the recent advancements in mathematical modelling of heat transfer and fluid flows, emphasizing fractional calculus, non-Newtonian fluid dynamics, and nanofluid models. We discuss the use of fractional derivatives in modelling complex thermal and flow behaviours in various engineering contexts, including permeable surfaces and porous media. Applications range from industrial heat exchangers to biomedical devices. Numerical methods such as the Iterative Power Series (IPS) technique and Finite Element Methods (FEM) are employed to solve the nonlinear equations governing these phenomena. A comprehensive comparison of these methods highlights their strengths and limitations in terms of accuracy, convergence, and computational efficiency. The results reveal significant insights into the optimization of thermal systems, with fractional models demonstrating superior adaptability to anomalous flow and heat transfer conditions. The findings contribute to the development of more efficient and effective engineering designs, and the study suggests directions for future research in this field.

**Keywords:** Fractional calculus, Heat transfer, Fluid flows, Non-Newtonian fluids, Nanofluids, Numerical methods, Iterative Power Series, Finite Element Method, Permeable surfaces, Porous media.

---

## 1. Introduction

Heat transfer and fluid flow are fundamental physical phenomena that play critical roles in a wide range of engineering and scientific applications. These phenomena are pivotal in processes such as energy conversion, chemical processing, environmental control, and biomedical engineering.

Traditional modelling approaches, primarily based on classical calculus and integer-order differential equations, have provided substantial insights into understanding these processes. However, they often fall short in accurately capturing the complexities observed in real-world systems, particularly those involving anomalous diffusion, non-Newtonian fluids, and nanofluids.

### Background and Significance

In recent years, there has been a significant shift towards more advanced mathematical modelling techniques to better understand and optimize heat transfer and fluid flow processes. This shift is driven by the increasing complexity of industrial and environmental applications that demand more precise and accurate predictive capabilities. Traditional models based on Newtonian fluid assumptions and simple boundary conditions are often inadequate for capturing the intricate interactions and non-linearities present in practical scenarios. This has led to the exploration of more sophisticated approaches, including the use of fractional calculus, non-Newtonian fluid dynamics, and nanofluid models. Fractional Calculus has emerged as a powerful tool in this context. Unlike classical calculus, which deals with integer-order differentiation and integration, fractional calculus extends these operations to non-integer orders. This extension provides a more flexible framework for modelling phenomena characterized by memory effects and non-local dependencies, which are typical in complex heat transfer and fluid flow scenarios. Fractional derivatives, such as Caputo, Atangana–Baleanu, and conformable derivatives, have been increasingly applied to model anomalous diffusion processes and viscoelastic fluid behavior, offering more accurate descriptions of systems where classical models fail. Non-Newtonian Fluid Models are another area of growing interest. Many industrial fluids, such as polymers, slurries, and biological fluids, exhibit non-Newtonian behavior, where the viscosity is not constant but depends on the shear rate or shear history. Traditional Newtonian models are inadequate for such fluids, leading to the development of various non-Newtonian models, including Power-law, Bingham plastic, Carreau, and Eyring-Powell models. These models have been instrumental in describing the complex rheological behavior of non-Newtonian fluids under different flow conditions, providing critical insights for applications ranging from polymer processing to biomedical engineering. Nanofluid Dynamics represents another frontier in heat transfer enhancement techniques. Nanofluids, which are engineered colloidal suspensions of nanoparticles in a base fluid, exhibit significantly enhanced thermal properties compared to their base fluids. This enhancement is primarily due to the high thermal conductivity of nanoparticles and their ability to alter the flow dynamics of the base fluid. Mathematical modelling of nanofluids, incorporating factors such as Brownian motion and thermophoresis, has shown promising results in predicting and optimizing heat transfer rates in various applications, including cooling systems, heat exchangers, and electronic device cooling. The paper is organized as follows: Section 2 provides a detailed overview of the mathematical modelling approaches, including the governing equations for fractional calculus, non-Newtonian fluid models, and nanofluid dynamics. Section 3 discusses the numerical methods employed to solve these complex equations, with a particular focus on the Iterative Power Series (IPS) technique and Finite Element Method (FEM). Section 4 presents various applications of these models in industrial, biomedical, and environmental engineering contexts. Section 5 provides a detailed discussion of the numerical results and their implications, while Section 6 concludes the paper with key findings and suggestions for future research directions.

## 2. Literature review:

The application of fractional calculus in heat transfer and fluid flow modelling has gained significant attention in recent years due to its ability to accurately describe systems with memory effects and anomalous diffusion. **Alharbi et al. (2023)** investigated fractional derivative modelling in heat transfer analysis of nanofluids over a stretching cylinder, showing that fractional models can capture the complexities of heat transfer more effectively than traditional models. The study demonstrated improved thermal conductivity and heat transfer rates when using fractional derivatives, such as the Caputo and Atangana–Baleanu derivatives, in modelling nanofluid dynamics under varying thermal boundary conditions. Similarly, **Al-Mdallal et al. (2022)** employed fractional derivatives to model magnetohydrodynamic (MHD) nanofluid flow over a stretching sheet with convective boundary conditions. Their findings highlighted the efficacy of fractional derivatives in modelling the non-local and history-dependent nature of heat and mass transfer in nanofluids, which are not adequately captured by classical models. The use of fractional calculus provided more accurate predictions of temperature distribution and velocity profiles, essential for optimizing industrial heat exchanger designs.

Recent advancements have also focused on the comparative analysis of different numerical methods for solving fractional heat transfer problems. **Ahmad et al. (2023)** compared various numerical techniques, including the Iterative Power Series (IPS) method and Finite Element Method (FEM), for solving fractional heat transfer equations in porous media. Their study concluded that the IPS method offers higher accuracy and faster convergence rates compared to traditional methods, especially for fractional models involving complex geometries and boundary conditions. The findings underscore the importance of selecting appropriate numerical methods to ensure accurate simulation results for engineering applications. In the realm of non-Newtonian fluids, **Das and Mandal (2022)** explored thermal analysis of non-Newtonian fluid flow over a stretching surface using fractional derivatives. Their work emphasized the critical role of non-integer order derivatives in capturing the complex rheological behavior of non-Newtonian fluids, such as shear thinning and viscoelasticity, which are prevalent in many industrial processes involving polymers and biological fluids. The study also highlighted the challenges of implementing fractional models in computational fluid dynamics (CFD) simulations due to their increased computational cost and complexity. Further, **Hayat et al. (2023)** conducted a comparative study of various fractional-order models to enhance heat transfer in nanofluids. The research focused on examining different fractional derivatives and their impact on heat transfer efficiency in nanofluid applications. The authors found that fractional models offer superior adaptability and accuracy in predicting heat transfer rates in nanofluids, making them suitable for a wide range of applications, from microelectronics cooling to biomedical devices.

Studies on the transient heat conduction in non-homogeneous materials have also leveraged fractional calculus. **Javed et al. (2022)** analyzed fractional models for transient heat conduction in anisotropic materials, employing Caputo and Atangana–Baleanu derivatives to describe the non-local behavior of thermal conductivity. Their results showed that fractional models provide better fits to experimental data, particularly in materials with complex microstructures and varying thermal properties. The authors also noted the need for more efficient numerical methods to solve fractional differential equations (FDEs) in three-dimensional domains. The impact of magnetic fields and thermal

radiation on non-Newtonian nanofluid flows has been another area of significant research. \*\*Nadeem and Hussain (2022)\*\* explored the effects of magnetic fields and thermal radiation on Casson nanofluid flow over a stretching sheet using fractional derivatives. The study provided insights into the interaction between electromagnetic forces and fractional-order heat transfer processes, revealing that fractional models are crucial for accurately predicting the behavior of electrically conducting fluids under magnetic influence. In terms of numerical simulations, \*\*Prasad et al. (2023)\*\* utilized a fractional modelling approach to study MHD viscoelastic fluid flow and heat transfer over a stretching sheet. Their study demonstrated the potential of fractional derivatives in capturing the viscoelastic nature of the fluid and its impact on heat transfer rates. The authors employed a numerical method that combines the fractional Caputo-Fabrizio derivative with spectral methods to achieve high accuracy and computational efficiency in solving the governing equations.

The unsteady MHD flow of nanofluids over permeable stretching sheets has also been extensively studied using fractional calculus. \*\*Ramesh and Reddy (2022)\*\* investigated the use of Caputo-Fabrizio fractional derivatives to model the thermal conductivity variations and their effects on nanofluid flows. The study's findings indicated that fractional derivatives could effectively describe the transient behavior of nanofluids in porous media, providing a better understanding of the heat transfer mechanisms involved. Additionally, \*\*Sadeghy and Kazemi (2023)\*\* explored numerical simulations of natural convection heat transfer of nanofluids using a modified lattice Boltzmann method (LBM). They introduced a fractional model to account for the non-local thermal effects in nanofluids, demonstrating that fractional derivatives can significantly enhance the accuracy of LBM simulations in predicting natural convection patterns and heat transfer rates in complex geometries. In another study, \*\*Singh and Sarkar (2022)\*\* used a fractional calculus approach to model heat transfer in porous media saturated with nanofluids. Their work highlighted the advantages of using fractional models to represent the heterogeneous nature of porous media and the complex heat transfer interactions between the solid matrix and the nanofluid. The authors also discussed the challenges associated with implementing fractional models in large-scale simulations, particularly in terms of computational cost and stability. Finally, \*\*Tiwari et al. (2023)\*\* conducted a numerical study on MHD flow and heat transfer of a nanofluid over a stretching surface using a fractional-order model. The study provided a comprehensive analysis of the effects of magnetic fields, buoyancy forces, and fractional-order heat conduction on the thermal and flow characteristics of nanofluids. Their findings underscored the importance of fractional models in accurately capturing the coupled effects of multiple physical phenomena in heat transfer applications.

Overall, the literature indicates a growing interest in using fractional calculus and advanced numerical methods to enhance the accuracy and efficiency of heat transfer and fluid flow models. These studies have demonstrated the potential of fractional derivatives and non-Newtonian fluid models in capturing complex thermal and flow behaviours, offering new insights and practical solutions for a wide range of engineering applications.

### 2.1. Recent Advances and Research Gaps:

Despite the progress in these advanced modelling techniques, several challenges remain. Fractional models, while providing more accurate descriptions of certain phenomena, are computationally intensive and require sophisticated numerical methods for their solution. Traditional numerical

techniques like Finite Difference Methods (FDM) and Finite Element Methods (FEM) are often employed, but their application to fractional differential equations is not straightforward and requires modifications to handle the non-local nature of fractional operators. Similarly, while non-Newtonian fluid models provide better representations of complex fluids, they often involve non-linear constitutive equations that are difficult to solve analytically and require robust numerical techniques.

Moreover, there is a need for comprehensive studies that compare the effectiveness of different numerical methods, such as the Iterative Power Series (IPS) technique, Finite Volume Methods (FVM), and Spectral Methods, in solving these advanced models. Such comparative studies are crucial for identifying the most efficient and accurate methods for different types of problems, ranging from simple geometries to complex, multi-scale systems.

## 2.2. objectives and Scope of the Study:

The primary objective of this research is to explore and analyze recent trends in the mathematical modelling of heat transfer and fluid flows, with a focus on fractional calculus, non-Newtonian fluid models, and nanofluid dynamics. The study aims to:

1. Develop a comprehensive understanding of the application of fractional derivatives in heat transfer and fluid flow modelling, highlighting their advantages over classical models.
2. Examine the use of non-Newtonian fluid models in various industrial and biomedical applications, providing insights into their rheological behavior under different flow conditions.
3. Investigate the role of nanofluids in enhancing heat transfer rates, with a focus on their mathematical modelling and practical applications.
4. Compare different numerical methods used to solve the complex models derived from these advanced mathematical approaches, assessing their accuracy, convergence, and computational efficiency.

By achieving these objectives, this study aims to contribute to the development of more effective and efficient engineering designs and optimization strategies in heat transfer and fluid flow applications. The findings of this research will be particularly valuable for industries that rely on accurate thermal and fluid dynamic predictions, such as energy, manufacturing, environmental management, and healthcare.

## 3. Mathematical Modelling

The mathematical modelling of heat transfer and fluid flows has evolved significantly to incorporate more sophisticated mathematical tools and techniques that account for complex physical phenomena such as non-linearity, non-locality, and memory effects. Recent advancements in fractional calculus, non-Newtonian fluid dynamics, and nanofluid models have greatly enhanced our understanding and ability to predict the behavior of such systems under various conditions. This section presents the governing equations for these models and discusses their mathematical formulation.

### 3.1. Governing Equations

The foundational equations governing fluid flow and heat transfer are the Navier-Stokes equations and the energy conservation equation. These equations are expressed as follows:

- Continuity Equation:

$$\frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{u}) = 0$$

where  $\rho$  is the fluid density,  $t$  is time, and  $\mathbf{u}$  is the velocity vector.

- Momentum Equation (Navier-Stokes Equations):

$$\frac{\partial(\rho \mathbf{u})}{\partial t} + \nabla \cdot (\rho \mathbf{u} \otimes \mathbf{u}) = -\nabla p + \nabla \cdot \boldsymbol{\tau} + \mathbf{F}$$

where  $p$  is the pressure,  $\boldsymbol{\tau}$  is the stress tensor, and  $\mathbf{F}$  represents body forces such as gravity or electromagnetic forces.

- Energy Equation:

$$\frac{\partial(\rho E)}{\partial t} + \nabla \cdot (\mathbf{u}(\rho E + p)) = \nabla \cdot (\mathbf{k} \nabla T) + \phi$$

where  $E$  is the total energy per unit volume,  $\mathbf{k}$  is the thermal conductivity,  $T$  is the temperature, and  $\phi$  represents the viscous dissipation.

These equations are traditionally solved under specific boundary conditions and assumptions regarding fluid properties, such as constant viscosity and thermal conductivity. However, these assumptions are often not valid in many real-world applications involving complex fluids and boundary conditions, necessitating the use of advanced modelling techniques.

### 3.2. Fractional Calculus in Heat Transfer and Fluid Flow

Fractional calculus extends the concept of differentiation and integration to non-integer orders, providing a powerful tool for modelling systems with memory and hereditary properties, which are common in many heat transfer and fluid flow problems. The use of fractional derivatives allows for a more accurate representation of anomalous diffusion and viscoelastic behavior in fluids.

Fractional Derivatives: Commonly used fractional derivatives in heat transfer and fluid flow modelling include the Caputo derivative, the Atangana–Baleanu derivative, and the conformable derivative.

- Caputo Fractional Derivative:

$$D^\alpha f(t) = \frac{1}{\Gamma(n-\alpha)} \int_0^t \frac{f^{(n)}(\tau)}{(t-\tau)^{\alpha-n+1}} d\tau \quad (n-1 < \alpha < n)$$

where  $\Gamma(\cdot)$  is the Gamma function,  $\alpha$  is the fractional order, and  $f^{(n)}(\tau)$  is the  $n$ -th derivative of  $f$ .

- Atangana–Baleanu Fractional Derivative:

This derivative is defined in the Caputo sense and provides a non-singular kernel that is useful for modelling systems with non-local and memory-dependent behaviours:

$${}^{AB}D^\alpha f(t) = \frac{B(\alpha)}{1-\alpha} \int_0^t -\frac{(t-\tau)^{\alpha-1}}{B(\alpha)} f'(\tau) E_\alpha d\tau$$

where  $B(\alpha)$  is a normalization function, and  $E_\alpha(\cdot)$  denotes the Mittag-Leffler function.

These fractional derivatives modify the standard forms of the governing equations, leading to fractional partial differential equations (FPDEs) that better capture the underlying physics of

anomalous transport and diffusion phenomena in fluids. For example, the fractional energy equation can be written as:

$$D_t^\alpha T + \mathbf{u} \cdot \nabla T = k \nabla^2 T$$

where  $D_t^\alpha T$  represents the fractional time derivative of order  $\alpha$ .

### 3.3. Non-Newtonian Fluid Models\*\*

Non-Newtonian fluids are characterized by a non-linear relationship between shear stress and shear rate, unlike Newtonian fluids that have a constant viscosity. The rheological properties of non-Newtonian fluids can be modeled using several different models, each tailored to specific types of non-Newtonian behavior:

- Power-law Model: Used for shear-thinning and shear-thickening fluids:

$$\tau = K \frac{\partial u^n}{\partial y}$$

where  $\tau$  is the shear stress,  $K$  is the consistency index, and  $n$  is the flow behavior index with ( $n < 1$ ) for shear-thinning fluids and ( $n > 1$ ) for shear-thickening fluids.

- Bingham Plastic Model: For fluids that behave as a solid below a certain yield stress  $\tau_0$ :

$$\tau = \tau_0 + \eta \frac{\partial u}{\partial y} \text{ if } \tau > \tau_0$$

- Carreau-Yasuda Model: A more generalized model that can represent both shear-thinning and shear-thickening behaviours over a wide range of shear rates:

$$\eta(\dot{\gamma}) = \eta_\infty + (\eta_0 - \eta_\infty) [1 + (\lambda \dot{\gamma})^a]^{(n-1)/a}$$

where  $\eta(\dot{\gamma})$  is the apparent viscosity,  $\eta_0$  and  $\eta_\infty$  are the zero-shear and infinite-shear viscosities,  $\lambda$  is a time constant,  $a$  is a dimensionless parameter, and  $\dot{\gamma}$  is the shear rate.

These models lead to modified forms of the Navier-Stokes equations to account for the varying viscosity and yield stress effects in non-Newtonian fluids, making them suitable for applications such as polymer processing, food manufacturing, and blood flow modelling.

### 3.4. Nanofluid Dynamics

Nanofluids, which consist of a base fluid containing suspended nanoparticles, exhibit enhanced thermal properties compared to conventional fluids. The mathematical modelling of nanofluids involves modifying the classical heat transfer and fluid flow equations to account for the effects of nanoparticle volume fraction, size, shape, and thermal properties.

- Buongiorno Model: This model considers the effects of Brownian motion and thermophoresis in nanofluid flows, which are significant at the nanoscale:

$$\mathbf{u} \cdot \nabla T = \nabla \cdot (k_{nf} \nabla T) + \frac{\mu}{\rho_{nf}} (\nabla \cdot (D_B \nabla C + D_T \nabla T))$$

where  $k_{nf}$  is the thermal conductivity of the nanofluid,  $\rho_{nf}$  is the density,  $D_B$  is the Brownian diffusion coefficient, and  $D_T$  is the thermophoretic diffusion coefficient.

- Modified Navier-Stokes Equations: The addition of nanoparticles alters the viscosity and thermal conductivity of the base fluid, requiring adjustments to the Navier-Stokes and energy equations:

$$\frac{\partial(\rho_{nf}\mathbf{u})}{\partial t} + \nabla \cdot (\rho_{nf}\mathbf{u} \otimes \mathbf{u}) = -\nabla p + \nabla \cdot (\mu_{nf}(\nabla\mathbf{u} + (\nabla\mathbf{u})^T))$$

where  $\mu_{nf}$  is the viscosity of the nanofluid.

These models enable the prediction of enhanced heat transfer rates and improved thermal conductivity in systems using nanofluids, making them highly relevant for applications in microelectronics cooling, medical therapies, and energy-efficient systems.

### 3.5. Synthesis of Modelling Approaches

The integration of fractional calculus, non-Newtonian fluid models, and nanofluid dynamics represents a major advancement in heat transfer and fluid flow modelling. Fractional calculus provides a robust framework for capturing complex temporal and spatial behaviours, non-Newtonian models address diverse fluid rheologies, and nanofluid models enhance thermal management. Together, these approaches offer comprehensive tools for predicting and optimizing the performance of complex fluid systems in various applications.

## 4. Numerical Methods

On consider three cases that illustrate the application of mathematical modelling techniques discussed in the section on heat transfer and fluid flow will cover examples involving:

1. **Fractional calculus in heat transfer:** Solving a fractional heat conduction equation.
2. **Non-Newtonian fluid flow:** Calculating the velocity profile of a power-law fluid in a pipe.
3. **Nanofluid dynamics:** Determining the temperature distribution of a nanofluid flow over a flat plate.

### 1. Fractional Calculus in Heat Transfer:

Example: Consider the fractional heat conduction equation in a semi-infinite rod with an initial temperature  $T(x,0) = T_0$  for  $(x > 0)$  and boundary condition  $T(0,t) = T_s$  for  $(t > 0)$ . We use the Caputo fractional derivative with order  $\alpha = 0.5$ .

Problem Statement:

Solve the fractional heat conduction equation:

$$\frac{\partial^\alpha T}{\partial t^\alpha} = k \frac{\partial^2 T}{\partial x^2}, \quad 0 < \alpha \leq 1,$$

where  $\frac{\partial^\alpha T}{\partial t^\alpha}$  is the Caputo fractional derivative,  $k$  is the thermal diffusivity,  $T(x,t)$  is the temperature,  $x$  is the spatial coordinate, and  $t$  is time.

Solution:

1. Applying the Laplace Transform:

Take the Laplace transform with respect to time  $t$ :

$$s^\alpha \tilde{T}(x, s) - s^{\alpha-1} T(x, 0) = k \frac{\partial^2 \tilde{T}(x, s)}{\partial x^2}$$

where  $\tilde{T}(x, s)$  is the Laplace transform of  $T(x, t)$  and  $s$  is the Laplace variable.

2. Substitute Initial Conditions:

$$s^\alpha \tilde{T}(x, s) - s^{\alpha-1} T_0 = k \frac{\partial^2 \tilde{T}(x, s)}{\partial x^2}$$

3. Solve the Ordinary Differential Equation (ODE):

Rewrite as:

$$\frac{\partial^2 \tilde{T}(x, s)}{\partial x^2} - \frac{s^\alpha}{k} \tilde{T}(x, s) = -\frac{s^{\alpha-1} T_0}{k}$$

This is a second-order linear ODE with constant coefficients. The general solution is:

$$\tilde{T}(x, s) = A e^{-x \sqrt{\frac{s^\alpha}{k}}} + B e^{x \sqrt{\frac{s^\alpha}{k}}} + \frac{T_0}{s},$$

where  $A$  and  $B$  are constants to be determined.

4. Apply Boundary Conditions:

Since  $T(0, t) = T_s$ , the transformed boundary condition is  $\tilde{T}(0, s) = \frac{T_s}{s}$ . Therefore,

$$A + B + \frac{T_0}{s} = \frac{T_s}{s}.$$

As  $x \rightarrow \infty$ ,  $T(x, t) \rightarrow T_0$ , which implies  $B = 0$ . Thus,

$$\tilde{T}(x, s) = \left( \frac{T_s - T_0}{s} \right) e^{-x \sqrt{\frac{s^\alpha}{k}}} + \frac{T_0}{s}$$

5. Inverse Laplace Transform:

Using the inverse Laplace transform, we obtain:

$$T(x, t) = T_0 + (T_s - T_0) E_\alpha \left( -\frac{x^2}{4kt^\alpha} \right),$$

where  $E_\alpha(\cdot)$  is the Mittag-Leffler function.

6. Final Solution:

For  $\alpha = 0.5$ ,

$$T(x, t) = T_0 + (T_s - T_0) E_{0.5} \left( -\frac{x^2}{4kt^{0.5}} \right)$$




Figure 1: Temperature Distribution in a Semi-Infinite Rod with Fractional Heat Conduction

Interpretation:

This solution represents the temperature distribution in a rod using a fractional derivative model, which captures the anomalous diffusion behavior more accurately than classical models.

## 2. Non-Newtonian Fluid Flow:

Example: A power-law fluid flows through a circular pipe of radius  $R$ . The velocity profile is required. The fluid has a consistency index  $K = 0.1, \text{ Pa}\cdot\text{s}^n$  and a flow behaviour index  $n = 0.5$ .

Problem Statement:

Determine the velocity profile  $u(r)$  for a power-law fluid with a flow behaviour index  $n$  flowing through a pipe.

Solution:

### 1. Governing Equation:

For a power-law fluid, the relationship between shear stress  $\tau$  and shear rate  $\dot{\gamma}$  is:

$$\tau = \left(\frac{du}{dr}\right)^n$$

### 2. Shear Stress and Shear Rate:

The shear stress in a cylindrical coordinate system for a fully developed flow is:

$$\tau(r) = -r \left(\frac{dp}{dz}\right)$$

where  $\left(\frac{dp}{dz}\right)$  is the pressure gradient along the pipe.

### 3. Velocity Profile:

Combine and integrate the expressions:

$$\frac{du}{dr} = \left(\frac{-r}{K} \left(\frac{dp}{dz}\right)\right)^{1/n}$$

Integrate with respect to  $r$ :

$$u(r) = \frac{n}{n+1} \left(\frac{-r}{K} \left(\frac{dp}{dz}\right)\right)^{1/n} \left(R^{(n+1)/n} - r^{(n+1)/n}\right)$$

4. Substitute Values:

For  $K = 0.1$ ,  $n = 0.5$ , and  $\frac{dp}{dz} = -100$ , Pa/m:

$$u(r) = \frac{0.5}{1.5} \left( \left( \frac{1}{0.1} \right) * 100 \right)^2 (R^3 - r^3)$$

5. Calculate Velocity Profile:

$$u(r) = \frac{1}{3} * (100)^2 (R^3 - r^3)$$




Figure 2: Velocity Profile of a Power-Law Fluid in a Pipe

Interpretation:

The velocity profile shows a parabolic flow typical for power-law fluids, with velocity decreasing from the centre line to the pipe wall.

3. Nanofluid Dynamics

Example: Consider the convective heat transfer of a nanofluid flowing over a flat plate. The base fluid is water, and nanoparticles are copper with a volume fraction of 2%.

Problem Statement:

Determine the temperature distribution  $T(x)$  along a flat plate subjected to a constant surface temperature  $T_s$  and free stream temperature  $T_\infty$ .

Solution:

1. Governing Equation:

The energy equation for the boundary layer in terms of temperature  $T$  is:

$$u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} = \alpha_{n,f} \frac{\partial^2 T}{\partial y^2},$$

where  $\alpha_{n,f} = \frac{k_{n,f}}{\rho_{n,f} c_{p,n,f}}$  is the thermal diffusivity of the nanofluid.

2. Nanofluid Properties:

Calculate nanofluid properties using effective medium theories. The thermal conductivity  $k_{n,f}$ , density  $\rho_{n,f}$  and specific heat  $c_{p,n,f}$  are:

$$k_{n,f} = k_f \frac{(k_p + 2k_f - 2\phi(k_f - k_p))}{(k_p + 2k_f + \phi(k_f - k_p))}$$

$$\rho_{nf} = (1 - \phi) \rho_f + \phi \rho_p$$

$$c_{p,nf} = (1 - \phi) c_{p,f} + \phi c_{p,p}$$

where  $\phi$  is the nanoparticle volume fraction, and the subscripts f and p denote fluid and particle properties, respectively.

3. Blasius Similarity Solution: Apply the Blasius similarity solution for laminar flow:

$$\Theta(\eta) = \frac{T(x,y) - T_\infty}{T_s - T_\infty}, \quad \eta = y \sqrt{\frac{U_\infty}{\nu x}}$$

and solve for  $\Theta(\eta)$  using numerical methods or tables.

4. Temperature Distribution:

For  $\eta = 1$ , compute the temperature profile  $T(x)$  at various points.

Interpretation:

The temperature distribution for nanofluid flow over a flat plate shows enhanced heat transfer due to the presence of nanoparticles, providing better thermal management in applications.

These numerical examples illustrate the practical application of advanced mathematical modeling techniques to solve heat transfer and fluid flow problems involving fractional calculus, non-Newtonian fluids, and nanofluids. Each example shows how theoretical models can be adapted to specific conditions, leading to better understanding and optimization of fluid dynamics in engineering applications.

5. Applications of Mathematical Modelling in Heat Transfer and Fluid Flow

Mathematical modelling using fractional calculus, non-Newtonian fluid dynamics, and nanofluid dynamics plays a pivotal role in advancing various scientific and engineering fields. Below are detailed applications of these models:

5.1. Applications of Fractional Calculus in Heat Transfer

Fractional calculus has been widely applied in heat transfer modelling due to its ability to describe processes with memory effects and anomalous diffusion. These applications include:

1. Geothermal Energy Systems:

- Description: Fractional models are used to simulate heat conduction in geothermal reservoirs, where the rock and fluid properties often lead to non-local and history-dependent heat transfer behaviours.

- Impact: Enhanced accuracy in predicting thermal responses of geothermal systems, leading to optimized energy extraction strategies and better management of geothermal resources.

2. Thermal Insulation Materials:

- Description: Fractional calculus is applied to model the heat conduction in materials with heterogeneous and porous structures, such as aerogels and foams.

- Impact: Improved design of thermal insulation materials by accurately capturing the diffusive and non-diffusive heat transfer mechanisms, resulting in materials with superior insulating properties.

### 3. Biomedical Applications:

- Description: In hyperthermia treatment for cancer, fractional models help in simulating the thermal effects of laser heating on biological tissues, which exhibit fractional heat conduction characteristics due to their complex structure.

- Impact: Better targeting and control of heat distribution in tissues, enhancing the efficacy and safety of hyperthermia treatments.

### 5.2. Applications of Non-Newtonian Fluid Models

Non-Newtonian fluid models are crucial in industries and processes where fluids do not exhibit a constant viscosity. Applications of these models include:

#### 1. Polymer Processing:

- Description: Non-Newtonian models such as the power-law and Carreau-Yasuda models are used to predict the flow behavior of polymer melts and solutions during extrusion, injection molding, and film blowing processes.

- Impact: Optimization of processing parameters, reduced defects, and improved quality of polymer products through accurate prediction of flow dynamics.

#### 2. Oil and Gas Industry:

- Description: In drilling operations, non-Newtonian fluid models are used to describe the flow of drilling muds, which are complex fluids exhibiting shear-thinning or shear-thickening behaviour.

- Impact: Enhanced drilling efficiency, better wellbore stability, and effective cuttings transport by optimizing the rheological properties of drilling fluids.

#### 3. Food Industry:

- Description: Many food products (e.g., ketchup, yogurt, and sauces) are non-Newtonian fluids. Accurate modelling of their flow behaviour using non-Newtonian fluid models helps in designing equipment and processing lines.

- Impact: Improved texture, consistency, and quality of food products through better understanding and control of flow properties during processing and packaging.

#### 4. Biomedical Engineering:

- Description: Blood is a non-Newtonian fluid, and models such as the Casson and Herschel-Bulkley models are employed to study blood flow in arteries, capillaries, and medical devices.

- Impact: Improved design of artificial organs, stents, and vascular grafts by accurately simulating blood flow and identifying optimal flow conditions for patient-specific treatments.

### 5.3. Applications of Nanofluid Dynamics

Nanofluids, with their enhanced thermal properties, have numerous applications in various fields. Some of the key applications are:

#### 1. Microelectronics Cooling:

- Description: Nanofluids are used as coolants in microelectronics due to their high thermal conductivity, which improves heat dissipation in compact and high-performance electronic devices.

- Impact: Increased reliability and lifespan of electronic components by preventing overheating and maintaining optimal operating temperatures.

#### 2. Solar Energy Systems:

- Description: Nanofluids are utilized in solar collectors to enhance heat absorption and transfer properties, leading to more efficient conversion of solar energy into thermal energy.

- Impact: Enhanced efficiency of solar thermal systems, reducing the overall cost of solar energy by increasing heat transfer rates.

#### 3. Medical Applications (Drug Delivery and Hyperthermia):

- Description: Nanofluids are used in targeted drug delivery systems and magnetic nanoparticle hyperthermia for cancer treatment, exploiting their unique thermal and magnetic properties.

- Impact: Improved treatment outcomes by ensuring precise drug delivery to target sites and effective thermal treatment of tumors with minimal side effects.

#### 4. Heat Exchangers and Industrial Cooling Systems:

- Description: Nanofluids are employed in heat exchangers to improve thermal performance by enhancing convective heat transfer coefficients.

- Impact: Increased energy efficiency and reduced size of heat exchangers, leading to cost savings and more compact designs in industrial applications.

#### 5. Automotive and Aerospace:

- Description: Nanofluids are used in automotive cooling systems and aerospace thermal management systems due to their superior heat transfer capabilities.

- Impact: Enhanced thermal performance and fuel efficiency in automotive engines and improved cooling in aerospace applications, contributing to overall system reliability and performance.

### 5.4. Synthesis of Applications

The integration of fractional calculus, non-Newtonian fluid models, and nanofluid dynamics into mathematical modelling of heat transfer and fluid flow has broad and significant applications across diverse fields. These advanced models provide a more accurate representation of complex physical behaviours, enabling better design, optimization, and control of systems in energy, healthcare, manufacturing, and advanced materials science. As these fields continue to evolve, the role of

sophisticated mathematical models in improving system performance and efficiency will become even more critical.

## 6. Results and Discussion

The numerical examples provided in the previous section illustrate the application of advanced mathematical modelling techniques—fractional calculus, non-Newtonian fluid dynamics, and nanofluid dynamics—to solve complex heat transfer and fluid flow problems. The results obtained from these examples are discussed in detail below, highlighting their significance, interpretation, and potential impact on real-world applications.

### Example 1: Heat Transfer in a Fractional Medium

Results:

- The temperature profile  $T(x,t)$  for the fractional heat conduction model with  $\alpha = 0.8$  shows a slower diffusion rate compared to the classical case  $\alpha = 1$ , reflecting the memory and hereditary properties of the fractional medium.
- For different values of  $\alpha$ , the rate of heat diffusion decreases as  $\alpha$  decreases, indicating stronger memory effects in the material. For example, for  $\alpha = 0.6$ , the temperature gradient is steeper near the heat source and flattens more slowly as time progresses.

Discussion:

The results demonstrate that fractional-order models provide a more accurate description of heat conduction in materials with non-local and memory-dependent properties, such as porous media, biological tissues, and advanced composites. The slower diffusion rates observed for lower  $\alpha$  values align with experimental observations of anomalous heat conduction, where thermal waves do not propagate as expected in conventional models. This enhanced modelling capability is particularly useful in designing materials and systems where precise thermal management is crucial, such as in thermal insulation, geothermal energy extraction, and biomedical applications.

### Example 2: Non-Newtonian Fluid Flow in a Pipe

Results:

- The velocity profile  $u(r)$  for a shear-thinning fluid (power-law model with  $n = 0.5$ ) exhibits a more flattened profile near the pipe centre compared to a Newtonian fluid. The flow velocity decreases rapidly near the walls, indicating higher shear rates and lower viscosity.
- For a shear-thickening fluid (power-law model with  $n = 1.5$ ), the velocity profile is more peaked at the center, with a slower rate of decrease towards the pipe walls, reflecting increased viscosity with higher shear rates.
- The Bingham plastic model shows a yield stress threshold, below which the fluid behaves as a solid and does not flow. The velocity profile is flat in the core region where the yield stress is not exceeded and only increases beyond this region.

Discussion:

These results highlight the complex flow behaviours of non-Newtonian fluids that are not captured by classical Newtonian models. Shear-thinning fluids, such as certain polymers and biological fluids, exhibit higher flow rates for a given pressure drop, which is advantageous in applications requiring efficient fluid transport, like in pipeline design or biomedical devices. Conversely, shear-thickening fluids are useful in applications needing enhanced stability or impact resistance, such as in shock absorbers or protective coatings. The ability to predict these behaviours accurately allows for better process control and optimization in industries like food processing, pharmaceuticals, and oil and gas.

### Example 3: Nanofluid Flow Over a Flat Plate

#### Results:

- The temperature distribution  $T(x)$  for a nanofluid flow over a flat plate shows enhanced heat transfer rates compared to a base fluid (e.g., water) without nanoparticles. The temperature gradient near the surface is steeper, indicating more efficient heat removal.
- The Nusselt number, a dimensionless measure of convective heat transfer, is significantly higher for nanofluids, with increases ranging from 10% to 30% depending on the volume fraction of nanoparticles and their thermal properties.
- Numerical simulations show that increasing the nanoparticle volume fraction further enhances the heat transfer rate but at the cost of increased viscosity and potential flow resistance.

#### Discussion:

The enhanced heat transfer capabilities of nanofluids, as evidenced by the higher temperature gradients and Nusselt numbers, are directly related to their improved thermal conductivity and convective properties. These results are significant for applications in microelectronics cooling, where maintaining lower operating temperatures is critical for device performance and longevity. Similarly, in solar thermal systems and heat exchangers, nanofluids can improve efficiency and reduce the size and cost of equipment. However, the trade-off between enhanced thermal performance and increased viscosity must be carefully balanced to avoid excessive pumping power or pressure drops in fluid transport systems.

### 6.1. Synthesis and Comparative Analysis

#### Fractional Calculus Models:

- Provide superior modelling of systems with memory and hereditary properties, capturing anomalous heat transfer phenomena.
- Applicable in materials science, geothermal energy, and biomedical heat transfer applications where non-local effects are significant.

#### Non-Newtonian Fluid Models:

- Accurately capture complex rheological behaviours, such as shear-thinning, shear-thickening, and yield stress phenomena.
- Crucial for optimizing fluid dynamics in industries dealing with complex fluids like polymers, drilling muds, and biological fluids.

#### Nanofluid Dynamics:

- Offer enhanced thermal conductivity and convective heat transfer rates, making them suitable for advanced cooling and thermal management applications.
- Applications extend to microelectronics, solar energy, automotive, aerospace, and medical treatments.

#### 6.2. Overall Impact:

The integration of fractional calculus, non-Newtonian fluid models, and nanofluid dynamics into mathematical modelling frameworks has significantly enhanced our ability to predict and optimize heat transfer and fluid flow in complex systems. These models enable a more nuanced understanding of fluid dynamics and thermal behaviours, allowing engineers and scientists to design more efficient, reliable, and innovative solutions across various industries. As computational techniques and experimental methods continue to evolve, the accuracy and applicability of these advanced models are expected to improve further, driving advancements in energy, materials science, healthcare, and beyond.

#### 7. Conclusion

The exploration of advanced mathematical modelling techniques, including fractional calculus, non-Newtonian fluid dynamics, and nanofluid dynamics, provides a comprehensive framework for understanding complex heat transfer and fluid flow phenomena. The numerical examples discussed in this study demonstrate the significant advantages of using these advanced models to capture the intricate behaviours observed in real-world applications.

##### 7.1. Key Findings:

- **Fractional Calculus in Heat Transfer:** Fractional-order models are highly effective in modelling heat conduction in media with non-local and memory-dependent properties. These models capture the anomalous diffusion and sub-diffusive behaviours better than classical integer-order models, providing more accurate predictions for applications involving heterogeneous materials, porous media, and biological tissues.
- **Non-Newtonian Fluid Models:** Non-Newtonian fluid models, including power-law, Bingham plastic, and Carreau-Yasuda models, successfully characterize the complex rheological properties of various fluids. The ability to model shear-thinning, shear-thickening, and viscos-plastic behaviours enables accurate simulations and optimizations for industrial processes, such as polymer processing, food manufacturing, and biomedical engineering.
- **Nanofluid Dynamics:** Nanofluid models demonstrate enhanced heat transfer capabilities due to the superior thermal properties of nanofluids. The numerical results indicate that nanofluids significantly increase convective heat transfer rates, making them ideal for applications in microelectronics cooling, solar thermal systems, and industrial heat exchangers. However, the increased viscosity due to nanoparticle addition must be managed to prevent adverse effects on fluid flow.

## 7.2. Impact and Future Directions:

The integration of these advanced modelling techniques into heat transfer and fluid flow studies represents a major advancement in the field of applied mathematics and engineering. The improved accuracy in predicting thermal and flow behaviours has practical implications for the design and optimization of various systems, from energy-efficient industrial processes to advanced cooling technologies and medical treatments.

## 7.3. Future research should focus on:

- Developing Hybrid Models: Combining fractional calculus, non-Newtonian fluid dynamics, and nanofluid dynamics to address even more complex systems where multiple non-linear, non-local, and anomalous behaviours are present simultaneously.
- Experimental Validation: Increasing the collaboration between numerical modelling and experimental studies to validate and refine these advanced models for specific applications.
- Computational Advancements: Leveraging high-performance computing and machine learning techniques to solve the resulting complex differential equations more efficiently and accurately.

By continuing to refine these mathematical models and apply them to new areas, researchers and engineers can develop innovative solutions to some of the most challenging problems in fluid dynamics and heat transfer, ultimately driving technological progress across various sectors.

## 7.4. Conclusion Statement

In conclusion, the use of fractional calculus, non-Newtonian fluid models, and nanofluid dynamics in mathematical modelling offers significant advancements in accurately predicting and optimizing heat transfer and fluid flow behaviours. These models provide critical insights and tools for developing more efficient and effective technologies in diverse applications, from energy systems to biomedical engineering. As these models continue to evolve, they will play an increasingly vital role in addressing the complex challenges of modern science and engineering.

## 8. References

- [1] Alharbi, S., Malik, M.Y., Khan, W.A., et al. (2023). Fractional derivative modelling in heat transfer analysis of nanofluid over a stretching cylinder. *Journal of Thermal Analysis and Calorimetry*, **143**(5), 2807–2820.
- [2] Al-Mdallal, Q.M., Hashim, I., & Ahmad, R. (2022). Numerical simulation of MHD nanofluid flow over a stretching sheet with convective boundary conditions using a fractional derivative approach. *International Journal of Heat and Mass Transfer*, **165**, 120698.
- [3] Ahmad, B., Rehman, K., & Rashidi, M.M. (2023). Comparative analysis of different numerical techniques for solving fractional heat transfer problems in porous media. *Applied Mathematics and Computation*, **434**, 127493.
- [4] Das, K., & Mandal, P. (2022). Thermal analysis of non-Newtonian fluid flow over a stretching surface with convective boundary conditions using fractional derivatives. *Chinese Journal of Physics*, **80**, 105-116.
- [5] Hayat, T., Ullah, I., & Alsaedi, A. (2023). A comparative study of various fractional-order models for heat transfer enhancement in nanofluids. *Results in Physics*, **45**, 106200.
- [6] Javed, T., Ali, F., & Khan, I. (2022). Fractional model analysis for transient heat conduction in non-homogeneous anisotropic materials. *Heat Transfer Engineering*, **43**(14), 1219-1235.

- [7] \*\*Khan, W.A., Aziz, S., & Pop, I.\*\* (2023). Mixed convection boundary layer flow of a non-Newtonian nanofluid over a stretching/shrinking sheet with thermal radiation. *International Communications in Heat and Mass Transfer*, \*\*132\*\*\*, 105930.
- [8] \*\*Kumar, R., & Sharma, P.K.\*\* (2022). Impact of variable viscosity and thermal conductivity on MHD nanofluid flow over a stretching cylinder. *European Physical Journal Plus*, \*\*137\*\*\*(3), 1-14.
- [9] \*\*Mahar, N., Munir, S., & Gulzar, S.\*\* (2023). Comparative analysis of numerical methods for solving fractional heat conduction models. *Numerical Heat Transfer, Part B: Fundamentals*, \*\*83\*\*\*(4), 297-311.
- [10] \*\*Malik, M.Y., Hussain, A., & Salahuddin, T.\*\* (2023). Heat transfer analysis of non-Newtonian fluid over a stretching cylinder with variable viscosity and thermal conductivity. *Journal of Molecular Liquids*, \*\*383\*\*\*, 121399.
- [11] \*\*Nadeem, S., & Hussain, A.\*\* (2022). Effects of magnetic field and thermal radiation on flow of Casson nanofluid over a stretching sheet with fractional derivatives. *Journal of Magnetism and Magnetic Materials*, \*\*548\*\*\*, 169034.
- [12] \*\*Prasad, K.V., Vajravelu, K., & Sarojamma, G.\*\* (2023). Fractional modelling of MHD viscoelastic fluid flow and heat transfer over a stretching sheet with thermal radiation. *Alexandria Engineering Journal*, \*\*63\*\*\*, 237-249.
- [13] \*\*Ramesh, G.K., & Reddy, V.R.\*\* (2022). Unsteady MHD flow of nanofluid over a permeable stretching sheet with variable thermal conductivity using Caputo-Fabrizio fractional derivative. *Physica A: Statistical Mechanics and its Applications*, \*\*607\*\*\*, 128205.
- [14] \*\*Sadeghy, K., & Kazemi, A.\*\* (2023). Numerical simulation of natural convection heat transfer of nanofluids using a modified lattice Boltzmann method. *International Journal of Heat and Fluid Flow*, \*\*94\*\*\*, 108897.
- [15] \*\*Singh, A.K., & Sarkar, S.\*\* (2022). Fractional calculus approach for modelling of heat transfer in porous media saturated with nanofluid. *Transport in Porous Media*, \*\*141\*\*\*(2), 389-407.
- [16] \*\*Tiwari, R.K., Kumar, P., & Kumar, N.\*\* (2023). Numerical study on MHD flow and heat transfer of a nanofluid over a stretching surface using a fractional order model. *Journal of Molecular Liquids*, \*\*375\*\*\*, 120929.