

MAXIMIZING BENEFITS AND MINIMIZING RISKS: EXPLORING THE POTENTIAL OF AGRICULTURAL REUSE OF WASTEWATER

Saha JK and Yadava RBR

Faculty of Science, Tanta University, Sri Ganganagar, Rajasthan, India

Abstract: Water scarcity is a pressing concern worldwide, leading to the development of new management strategies to increase water supply. Among these strategies, wastewater treatment offers a green and sustainable solution to alleviate water crises. In this review, we find that the reuse of treated wastewater in high-demand water sector of irrigation is the most promising way to cope up with both water scarcity and wastewater disposal. However, properly managed wastewater treatment schemes that adhere to good agriculture practices and routine monitoring are essential to minimize negative health and environmental impacts. The reuse of treated wastewater provides reliable and cheap irrigation water supply, contributes to food security, reduces waste production, and improves environmental health. Moreover, adequate control of non-biodegradable and toxic industrial wastewater can solve significant issues. On the other hand, there are potential risks associated with the reuse of inadequately treated wastewater. These risks include contamination of the food chain, adverse health effects due to exposure to toxic and hazardous substances, soil salination or accumulation of unknown constituents, and degradation of groundwater quality. Therefore, before using treated sewage in agriculture, careful evaluation at the project planning stage, crop selection, and irrigation management should follow guidelines. Multidisciplinary research, training programs for treatment plant operators, and awareness programs for farmers can help in better management of health and environmental impacts.

Keywords: wastewater management, irrigation, environmental health, public health, treated wastewater, sewage treatment, agricultural reuse, beneficial reuse.

Introduction: One of the largest threats society is facing today is water scarcity. It is UN's main millennium development goals to cope up with this crisis. "By 2030, the country's water demand is projected to be twice the available supply, implying severe water scarcity for hundreds of millions of people and an eventual 6% loss in country's GDP," the report released by union minister for water resources (*Daily Pioneer, 10 July, 2018*). All governments have started to mitigate these effects by rain water harvesting, desalination, water location transfers and waste water treatment. Out of these, waste water treatment is a green and sustainable short term and long term solution to water crisis. Water reuse becomes even essential for water scarce states like Rajasthan, Maharashtra, and other states in India where water availability is highly critical. Earlier most of wastewater generated was discharged into water bodies like rivers, oceans etc. without any treatment and

resulted in pollution of these huge systems. Environmental protection agencies have now started to impose very strict regulatory prohibitions of wastewater treatment for attaining the discharge quality. Treatment plants just reduce the pollutant level in waste water to a level nature can handle.

Findings of wastewater reuse: The physicochemical and microbiological characters in the raw sewage are unacceptable and the treatment process reduces the undesirable characters to a sufficient extent and the sewage characteristics of treatment plants should be regularly monitored to know the pollutant levels upon the various time scales (Velusamy and Kannan 2016). Treated wastewater can be used for many purposes like irrigation of agriculture land, landscape irrigation, recreational activities, urban and industrial use, aquaculture and artificial ground water recharge (Asano et al. 2007). The treated waste water (TWW) can constitute a reliable water and nutrient source for crops (B. Jimenez-Cisneros 1995) and its use for irrigation reduces the amount of nutrient-rich water returned to rivers or sea. In comparison to applying ground water with fertilizers, application of the domestic waste water with fertilizers showed improvements in the crop yield and physicochemical properties of the soil besides slight changes in salt solubility and alkalinity on a clay soil (Singh, Deshbhratar and Ramteke 2012). Research conducted in Riyadh, Saudi Arabia on the reuse of treated municipal wastewater to determine the effect of irrigation on crop yield, plant composition and soil properties with special emphasis on accumulation of trace metals showed that treated municipal waste water can be used safely for irrigation of a selected group of crops (Ali A. Aljaloud 2010). It enriched the soil in minerals, increased plant nutrient uptake, promoted crop yield, & improved the overall profit. Developing countries are using treated wastewater mainly for crop irrigation (Kansal and Singh 1983; Bahri 1988).

Sewage and other industrial effluents are rich in organic matter and plant nutrients and find cheaper way of disposal in high water demand sector of agriculture (Nath *et al.*, 2009; Nagajyothi *et al.* 2009). Urban and peri-urban areas in most of the developing countries are using treated, poorly treated, diluted or even raw waste water for irrigation (Hamilton *et al.* 2007; Keraita *et al.* 2008; Scott *et al.* 2004). There are several advantage and disadvantage in using sewage water for irrigation purpose (Ramana *et al.* 2002; Saravanmoorthy and Kumari 2007). Sewage water is rich in plant nutrients that increase crop yield substantially and reduce the need for fertilizer. It ultimately decreases overall cost of production. Due to rich organic as well as inorganic matter (N,P,K) and other micronutrients sewage water application is a low priced fertilizer (Hundal and Sandhu 1990). According to Otobang *et al.* (1997) sewage sludge is used commonly as manure due to presence of multi-element organic wastes. Secondary treated wastewater finds safe application for root and leafy crops irrigation (Farhadkhani *et al.* 2018). Sewage waste water should not be continuously used as it may lead to many environmental problems like soil sickness and ground water contamination and phytotoxicity (Hicks and Hird 2000).

Socio-economic growth of a country demands industrial activities which in turn generate huge amounts of solid and liquid wastes. It is leading to more and more discharge of pollutants into the water environment such as rivers and lakes, and more water pollution disasters have happened. Improvement in soil properties due to soil waste interactions opens up the way to use the industrial wastes as soil stabilizers (Abhilash and Tharani, 2016). It becomes important to detect the pollution timely for conservation of water environment. It is the precondition to locate and find the pollution source as well. The wastewater characteristics mainly depend upon the living standards of the people, agricultural runoff, and commercial activities in the city. If industrial wastewater is included in influents of wastewater treatment facilities, then contaminant range becomes very broad (Ratola *et al.* 2012). Poorly treated wastewater will affect water users adversely and contaminate surface as well as ground water. Long term use of such water may have acute or cumulative toxic impacts. Monitoring

of physicochemical parameters of treated wastewater helps in safe release of final effluent as it is a health and environment concerned issue.

Kushwah et al. (2011) showed distinct seasonal variation in physicochemical parameters of the influent and effluent water and suggested continuous monitoring of STP. Evaluation of the final effluents of two wastewater treatment plants (WWTPs) in the Eastern Cape Province of South Africa for their physicochemical and microbiological qualities over a period of 12 months led to the conclusion that these WWTPs are important point sources of pollution in surface water with potential public health and ecological risks (Osuolale and Okoh 2015). Investigations of the wastewater pollution level by analyzing its chemical characteristics at five wastewater collectors remarked that pollution level greatly depends on the origin site of the wastewater (Popa and coworkers 2012). Correlation analysis was used in order to identify possible relationships between concentrations of various analyzed parameters, which could be used in selecting the appropriate method for wastewater treatment to be implemented at wastewater plants. Sugar Industries are the primary source of water pollution. The results of the study on composition of effluents of four sugar industries showed that the effluents in general exceed the limits specified by CPCB with reference to parameters such as BOD, COD, oil & greases, total suspended solids, so suggested recommended measures should be worked upon (Jadhav et al. 2013).

Research on the performance of Activated Sludge Wastewater Treatment Plant (ASWTP) investigated the level of effectiveness of the activated sludge process (Ukpong 2013). The result showed that wastewater had no smell with clear color at normal temperature and equilibrium pH value of 7. Wastewater treatment plant with this technique has good potential to produce high quality effluent on a continuous basis. Seven small wastewater treatment plants working on the principle of anaerobic pre-treatment and aerobic post-treatment were chosen (Gasparikova et al. 2005) for evaluation. An integrated system originated from the combination of anaerobic and aerobic technologies and following operational experiences it is concluded that the properly operated two-stage technology is effective for the removal of organic pollution and suspended solids. It confirmed the viability of an integrated anaerobic-aerobic system for municipal wastewater treatment, even in a country with a temperate climate. To study the seasonal differences of wastewater treatment employing screens, trickling filters and oxidation ponds, analysis of water samples from four different points was carried out (Cheboretal. 2017) during the dry and wet seasons. The researchers recorded lower figures for most of the parameters during wet season. Studies on treatment operations of 17 wastewater treatment plants (WTPs) in cold and hot climate were carried out, in order to examine their potential environmental impacts and assess their disposal options (Mahgoubetal. 2015). The results of the quality of wastewater in drainages that discharge from these WTPs distributed in the province of Al-Sharqiya, in Egypt indicated that the treatment plants had a significant role in pollution control. The results of 3-year study (2010– 2012) based on principal factor analysis technique (PFA) on two urban wastewater treatment plants (WWTPs) situated in Murcia, Southeast of Spain were presented (Bayo et al 2016). These findings show that to prevent any long term risk associated with human and environment, proper monitoring and continuous assessments of the secondary treated wastewater irrigation are required.

Treated wastewater irrigation of olive trees in arid and semi-arid regions is becoming a necessary alternative to address the issues of water shortage. The irrigation requires a careful monitoring of soil and plants for a range of parameters including salts, nutrients, microelements, heavy metals, toxic pollutants, and pathogens. A 3-years monitoring of the above parameters in soil and leaves of olive trees in Crete, Greece was conducted (Petousi et al. 2015) using trees that were irrigated with three types of water: secondary treated wastewater (STW), tertiary treated wastewater (TTW), and tap water (TW). The results of this study suggest that STW and TTW can be applied successfully for the safe irrigation of the olive groves. Physicochemical analysis of

the wastewater collected from rubber processing factory inferred substantial reduction in the solid concentration, BOD and COD, nitrate, phosphorus, and bacteria counts (Asia et al.2007) and inferred that treated effluent could be discharged safely into the environment without the fear of pollution.

Benefits of wastewater reuse

- No doubt, water treatment process produces clean reusable water. It ensures reliable and cheaper irrigation water supply.
- Treated water nutrient content is higher, so increased crop yield contributes to food security.
- If wastewater treatment schemes are properly managed, have high potential to reduce waste production and improve environmental health (Mara and Cairncross1989).
- Surface water pollution can be avoided and thus saves money spent on projects required to battle environmental pollution.
- Sludge produced during treatment process is used as manure (Otobbangetal.1997).
- Low cost drought-proof water supply reduces storage, water transfer, deslination etc. and makes local sourcing of water.
- Not only this, treatment plants can be a source of energy production. As-Samra WWTP in Jordan produces 40% of the energy required through burning the methane produced by treatment process. It helps making WWTP self-sustainable and reduces country's expenditure on energy production.

Potential Risks of wastewater reuse

- When the treatment is not adequate, potential risks are associated with reclaimed water reuse especially for irrigation. Food chain may get contaminated with pathogens (bacteria, virus, helminthus, protozoa). These pathogens may cause endemic or epidemic diseases especially when untreated wastewater irrigated foods are eaten uncooked (e.g. salad crops and some vegetables) (Shuval et al.1986). This was confirmed for geohelminthic and bacterial diseases by Blumenthal and Peasey (2002).
- Heavy metals like lead, cadmium, mercury etc. and many organic compounds (pesticides) cause health effects (cancers) on prolonged exposure. As the toxic and hazardous substance discharge is not controlled in the waste, it may cause lethal effects to consumers and environment.
- Soil may get salinated or various unknown constituents get accumulated in soil which may adversely affect agriculture. These may reduce crop yield either by directly inhibiting plant growth or indirectly by reducing the plants ability to absorb nutrients.
- Algae or other vegetation can grow in canals carrying treated water. Various contaminants may get accumulated in aquifers and ultimately leading to degradation of ground water quality.

Recommendations: The WHO's 2006 guidelines for the safe use of wastewater, excreta and grey-water constitute atool for the preventive management of wastewater in agriculture and provide clear guidelines for policy-makers on wastewater application in different local contexts. FAO has given guidelines to evaluate irrigation water quality applicable to the local conditions (Ayers and Westcot 1985). Further attention should be given to selection of crop and irrigation system. Attention should be paid on following points before deciding use of treated sewage in agriculture:

- Agrarian economy of India demands compulsory use of treated sewage for irrigation but should never be used for millet production and edible crops.
- Crop grown should be selected on the basis of type of soil and composition of treated sewage available (Ali A. Aljaloud 2010).
- Rotational crop pattern should be practiced for an all the year round utilization.

- Irrigation management is very important that is to irrigate only when it is required and also to the extent it is required by the crop. Deposition of nutrients, chemicals, pathogens or heavy metals in the soil and deep percolation risks can be reduced if surface ponding or stagnant effluents are avoided. For this, careful leveling and controlled water application by advanced irrigation systems (Humpherys 1986) should be practiced.

- The soil should be opened up by deep ploughing and cultivated properly before the next crop is raised.

Other Applications of Reclaimed Water

- Treated sewage can be used in many more ways other than agriculture and is being used in world and in many cities of India.

- Horticulture needs of green areas and emergency purpose like fire brigade should be met with treated sewage.

- An irrigation method for sewage fed tree plantation has been recommended by the Indian Agriculture Research Institute, Karnal.

- Special supply lines must be laid for TWW supply to new developing construction sites and it mandatory use TWW for construction activities.

- TWW price must be kept sufficient lower than fresh water price.

- Public fear about reuse system should be overcome through education and awareness program.

- From as early as 1991, the major Industries like Madras Refineries, Madras Fertilizers and GMR Vasari Power Plant, Chennai etc. are using secondary treated sewage in cooling water makeup.

- Major metropolitan cities like Bangalore, Chennai, Mumbai and Delhi are using treated grey water for toilet flushing in some of the high rise apartment complexes on a pilot scale.

Conclusion

Properly managed wastewater treatment schemes have high potential to reduce waste production and improve environmental health. To improve wastewater use in irrigation, good agriculture practices should essentially be adhered. Crop irrigation water used should always be in accordance with reference document on the physico-chemical quality of water, including wastewater, used for crop irrigation FAOs water quality for agriculture. There should be careful evaluation at the project planning stage and properly treated wastewater should be used for edible crops. Multidisciplinary research, training programs for the treatment plant operators and awareness programs for farmers would definitely help in better management of health and environmental impacts. Adequate control of non-biodegradable and toxic industrial wastewater can solve the issues to a great extent.

References

Abhilash P Teja, Tharani K (2016) Influence of Industrial Effluents on Properties of Soil. International Research Journal of Engineering and Technology 3(11):1491-1496 [2] Ali A Aljaloud (2010) Reuse of wastewater for irrigation in Saudi Arabia and its effect on soil and plant. 19thWorld Congress of Soil Science, Soil Solutions for a Changing World :163-166

Asano T, Burton FL, Leverenz H, Tsuchihashi R, and Tchobanoglous G (2007) Water Reuse: Issues, Technologies and Applications. New York, McGraw Hill

Asia IO and Akporhonor E (2007) Characterization and physicochemical treatment of wastewater from rubber processing factory. International Journal of Physical Sciences 2(3): 061-067

- Ayers RS, Westcot DW (1985) Water Quality for Agriculture. FAO Irrigation and Drainage Paper 29 Rev. 1, FAO, Rome
- Bahri A, (1988) Present and future state of treated wastewaters and sewage sludge in Tunisia. In: Presented at Regional Seminar on “Wastewater Reclamation and Reuse”, December 11–16, Cairo
- Bayo J, Ruiz-Martínez D, Carpe J & Lopez-Castellanos J, (2016) Assessing The Environmental Impact Of Wastewater Treatment Plants By Chemometric Approach. *Int. J. Sus. Dev. Plann. Proceedings of the 3rd International Conference on Environmental and Economic Impact on Sustainable Development (Environmental Impact 2016)* 11(2): 203–211
- Blumenthal UJ and Peasey A (2002) Critical Review of Epidemiological Evidence of Health Effects of Wastewater and Excreta in Agriculture (Background paper for the WHO Guidelines for the safe use of wastewater and excreta in agriculture). Geneva: World Health Organization
- Chebor J, Ezekiel K kiprop, Lizzy AM wamburi (2017) Effect of Seasonal Variation on Performance of Conventional Wastewater Treatment System. *Journal of Applied & Environmental Microbiology*, 5(1): 1-7
- Farhadkhani M. Nikaeen M, et al. (2018) Effects of irrigation with secondary treated wastewater on physicochemical and microbial properties of soil and produce safety in a semiarid area. *Water Research* 144: 356-364
- Gasparikova E, Kapusta S, Bodik I, Derko J, Kratochvil K (2005) Evaluation of Anaerobic –Aerobic Wastewater Treatment Plant Operation, *Polish Journal of Environmental Studies* 14(1): 29-34
- Hamilton AJ, Stagnitti F et al. (2007) Wastewater irrigation: the state of play. *Vadose Zone J* 6(4): 823-840
- Hicks RW, and Hird C (2000) *Soils: their properties and management* 2nd edition, edited by Charman PEV and Murphy BW (Oxford University Press):378-399
- Humpherys AS (1986) Automated J arm surface irrigation system worldwide. *International Standard Book No: 81-5086-13-5(ICID)*
- Hundal KS and Sandhu SS (1990) Effect of sewage water on soil properties and heavy metal accumulation. *Indian J. Ecology* 17(I): 42-47
- Jadhav PG, Dr. Vaidya NG, Deth SB (2013) Characterization and Comparative study of cane sugar Industry Waste Water. *International Journal of Chemical and Physical Sciences* 2(2):19-25
- Jimenez Cisneros B (1995) Wastewater reuse to increase soil productivity. *Water Science and Technology*. 32(12):173–180
- Kansal BD, and Singh J (1983) Influence of the municipal wastewater and soil properties on the accumulation of heavy metals in plants. In *Proceeding of International Conference of Heavy Metals in the Environment, Heidelberg, Germany, CEP Consultants, Edinburgh*, pp. 413– 416

- Keraita B, Jiménez B, Drechsel P (2008) Extent and implications of agricultural reuse of untreated, partly treated and diluted wastewater in developing countries. *CAB Reviews: Perspectives in Agriculture, Veterinary Science, Nutrition and Natural Resources* 3: 1-15
- Kushwah RK, Bajpaia A, Malik S and Singh A 2011 Seasonal Variation of Physicochemical Parameters of Waste Water From a Sewage Treatment Plant, Bhopal (India). *Int. J. Chem. Sci.* 9(3):1545-1552
- Mahgoub S, Samarasb P, Abdelbasit H, Abdelfattah H (2015). Seasonal variation in microbiological and physicochemical characteristics of municipal wastewater in Al-Sharqiya province, Egypt (case study). *Desalination and Water Treatment* 57(5):1–10
- Mara DD and Cairncross S (1989) *Guidelines for the Safe Use of Wastewater and Excreta in Agriculture and Aquaculture: Measures for Public Health Protection*. Geneva: World Health Organization
- Nag Jyothi PC, Dinakar N, Suresh S, Udaykiran Y, Suresh C and Damodharam T (2009) Effect of industrial effluent on the morphological parameters and chlorophyll content of green gram (*Phaseolusaureus* Roxb). *Journal of Environmental Biology* 30:385-388 [24] Nath K, Singh D, Shyam S, Sharma YK (2009) Phytotoxic Effects Of Chromium And Tannery Effluent On Growth And Metabolism Of *Phaseolus Mungo* Roxb. *Journal of Environmental Biology* 30(2):227-234
- Osuolale O and Okoh A (2015) Assessment of the Physicochemical Qualities and Prevalence of *Escherichia coli* and *Vibriosis* in the Final Effluents of Two Wastewater Treatment Plants in South Africa. *Ecological and Public Health Implications Int. J. Environ. Res. Public Health* 12:13399-13412.
- Otobbang E, Sadovnikova L, Lakimenko O, Nilsson I and Persson J (1997) Sewage sludge: Soil conditioner and nutrient source II Availability of Cu, Zn, Pb, and Cd to barley in a pot experiment. *Acta Agriculturae Scandinavica*”, Section B, Soil and Plant Science 47:65-70
- Petousi I, Fountoulakis MS, etal. (2015) Effects of reclaimed wastewater irrigation on olive (*Olea europaea* L. cv. ‘Koroneiki’) trees. *Agricultural Water Management* 160:33–40 [28] Popa P, Timofti M, etal. (2012) Study of Physico-Chemical Characteristics of Wastewater in an Urban Agglomeration in Romania. *The Scientific World Journal* 2012:0110
- Ramana S, Biswas AK, Kudus S, Saha JK, and Yadava RBR (2002) Effect of distillery effluent on seed germination in some vegetable crops. *Biorecourse Technology* 82: 273–275
- Ratola N, Cincinelli A, Alves A, Katsoyiannis A. Occurrence of organic micro contaminants in the wastewater treatment process-A mini review. *Journal of Hazardous Materials* 239–240:1-18
- Saravanmoorthy MD and Ranjitha KBD (2007) Effect of textile waste water on morpho-physiology and yield on two varieties of peanut (*Arachis hypogea* L.). *Journal of Agricultural Technology* 3:335–343
- Satyanarayan S, Venerkar AP, Ramakant, (2004) Organic removals from highly proteinous wastewater from soya milk and tofu manufacturing plant. *J. Environ Sci. Health.* 39(3):759-771

- Scott CA, Faruqui NI, Raschid-Sally L (2004) Wastewater use in irrigated agriculture: confronting the livelihood and environmental realities. CABI Publishing, Wallingford, UK
- Shuval HI, Adin A, Fattal B, Rawitz E, and Yekutieli P. (1986) Wastewater Irrigation in Developing Countries: Health Effects and Technical Solutions. Technical Paper No. 51. Washington, DC: World Bank
- Singh PK, Deshbhratar PB, Ramteke DS (2012) Effects of sewage wastewater irrigation on soil properties, crop yield and environment. *Agricultural Water Management* 103:100-104
- Ukpong EC (2013) Performance Evaluation of Activated Sludge Wastewater Treatment Plant (ASWTP) At QIT, Isbeno Local Government Area of Akwalbom State, Nigeria. *The International Journal of Engineering and Science* 2(7):01-13
- Velusamy K and Kannan J (2016) Seasonal Variation in Physico-Chemical and Microbiological Characteristics of Sewage Water from Sewage Treatment Plants. *Current World Environment* 11(3):791-799.